



P550490

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1 1/8-16 UN
Length	260 mm (10.24 inch)
Gasket OD	104 mm (4.09 inch)
Gasket ID	93 mm (3.66 inch)
Efficiency 50%	22 micron
Efficiency 99%	40 micron
Efficiency Test Std	ISO 16889
Bypass Valve	Yes

Bypass Valve Setting HR	2.5 bar (36 psi)
Media Type	Cellulose
Collapse Burst	10 bar (145 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	SCANIA 1117285

Other Information

UPC Code	742330115725
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.