

Product Specifications



P550719 LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	95 mm (3.74 inch)
Thread Size	1-12 UN
Length	107 mm (4.21 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4572
Bypass Valve	Yes
Bypass Valve Setting LR	1.4 bar (20 psi)

Bypass Valve Setting HR	1.7 bar (25 psi)
Collapse Burst	5.2 bar (75 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	CASE/CASE IH 3136046R93

Other Information

UPC Code	
----------	--

742330043158

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.