



P551102

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	110 mm (4.33 inch)
Thread Size	1 1/8-16 UN
Length	256 mm (10.08 inch)
Gasket OD	102 mm (4.02 inch)
Gasket ID	92 mm (3.62 inch)
Efficiency 50%	20 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	2.5 bar (36 psi)
Media Type	Cellulose
Collapse Burst	4 bar (58 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	DEUTZ 1174420

Other Information

UPC Code	742330043639
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.