

## B085056

### AIR FILTER, PRIMARY DURALITE

#### Why Choose Donaldson DuraLite™ Air Cleaners?

Rugged, lightweight, self-supporting, and completely disposable combination air cleaner and filter.

- Function well under severe pulsation conditions, particularly two- and three-cylinder engines.
- Vibration-resistant media is secured into molded housings of rugged ABS plastic—so they don't fall apart as other designs might.
- Easy to install, durable, and reliable.
- Completely disposable — acceptable for normal trash pick-up (DuraLite should not be incinerated).



#### Attributes

Outlet Diameter	150 mm (5.91 inch)
Body Diameter Maximum	196 mm (7.72 inch)
Body Length	260 mm (10.24 inch)
Efficiency	99.6%
Efficiency Test Std	ISO 5011
Rated Flow LR	27.5 m <sup>3</sup> /min (971 cfm)
Rated Flow MR	34.4 m <sup>3</sup> /min (1215 cfm)
Rated Flow HR	40 m <sup>3</sup> /min (1413 cfm)

Restriction LR	102 mm H2O (4.02 inch H2O)
Restriction MR	152 mm H2O (5.98 inch H2O)
Restriction HR	203 mm H2O (7.99 inch H2O)
Family	ECB
Primary Application	MAN 51083040015
Type	Primary
Style	Round
Brand	DuraLite™

---

#### Other Information

UPC Code	742330149423
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.