



Product Specifications

C085004

AIR FILTER, PRIMARY DURALITE

Why Choose Donaldson DuraLite™ Air Cleaners?

Rugged, lightweight, self-supporting, and completely disposable combination air cleaner and filter.

- Function well under severe pulsation conditions, particularly two- and three-cylinder engines.
- Vibration-resistant media is secured into molded housings of rugged ABS plastic—so they don't fall apart as other designs might.
- Easy to install, durable, and reliable.
- Completely disposable — acceptable for normal trash pick-up (DuraLite should not be incinerated).



Attributes

Outlet Diameter	76.2 mm (3.00 inch)
Body Diameter Maximum	215.9 mm (8.50 inch)
Body Length	241.3 mm (9.50 inch)
Efficiency Test Std	ISO 5011
Rated Flow LR	4.8 m ³ /min (170 cfm)
Rated Flow MR	5.8 m ³ /min (205 cfm)
Rated Flow HR	6.9 m ³ /min (244 cfm)
Restriction LR	102 mm H ₂ O (4.02 inch H ₂ O)

Restriction MR	152 mm H2O (5.98 inch H2O)
Restriction HR	203 mm H2O (7.99 inch H2O)
Family	ECC
Type	Primary
Style	Round
Brand	DuraLite™
Media Type	Cellulose

Other Information

UPC Code	742330000960
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.