

## P114931

### AIR FILTER, SAFETY



#### Why Choose Donaldson Safety Filters?

Safety filters have two functions: to act as a backup to the primary filter and to protect the engine during primary filter servicing.

- Serve as a backup filter in case of primary filter damage or improper installation.
- Prevent contaminants from entering the clean side of the air intake system during primary filter servicing.
- Designed to plug rapidly if contamination finds its way past the primary filter, alerting operators about an issue.
- Recommend that safety filters are replaced with every third primary filter change unless there has been a failure of the primary filter.

#### Attributes

Outer Diameter	219.96 mm (8.66 inch)
Inner Diameter	179.2 mm (7.06 inch)
Length	423.2 mm (16.66 inch)
Gasket ID	190.5 mm (7.50 inch)
Overall Length	432.9 mm (17.04 inch)
Efficiency	99.6
Efficiency Test Std	ISO 5011

Rated Flow LR	36 m <sup>3</sup> /min (1271 cfm)
Rated Flow HR	23 m <sup>3</sup> /min (812 cfm)
Family	STG
Primary Application	DONALDSON STG16
Type	Safety
Style	Round
Media Type	Safety

---

#### Other Information

UPC Code	742330009178
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.