

P124860

AIR FILTER, SAFETY

Why Choose Donaldson Safety Filters?

Safety filters have two functions: to act as a backup to the primary filter and to protect the engine during primary filter servicing.

- Serve as a backup filter in case of primary filter damage or improper installation.
- Prevent contaminants from entering the clean side of the air intake system during primary filter servicing.
- Designed to plug rapidly if contamination finds its way past the primary filter, alerting operators about an issue.
- Recommend that safety filters are replaced with every third primary filter change unless there has been a failure of the primary filter.



Attributes

| | |
|---------------------|-----------------------|
| Outer Diameter | 194.1 mm (7.64 inch) |
| Inner Diameter | 153.4 mm (6.04 inch) |
| Length | 457.2 mm (18.00 inch) |
| Bolt Hole Diameter | 22.73 mm (0.89 inch) |
| Efficiency Test Std | ISO 5011 |
| Family | FVG |
| Primary Application | TEREX 9031711 |

| | |
|------------|--------|
| Type | Safety |
| Style | Round |
| Media Type | Safety |

Other Information

| | |
|----------|--------------|
| UPC Code | 742330010730 |
|----------|--------------|

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.