

Product Specifications



P502458

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	102 mm (4.02 inch)
Thread Size	1-12 UN
Length	101 mm (3.98 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	88 mm (3.46 inch)
Efficiency 50%	17 micron
Efficiency 95%	27 micron
Efficiency 99%	39 micron
Efficiency Test Std	ISO 4548-12

Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	1 bar (15 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	MITSUBISHI 32A4000400

Other Information

UPC Code	742330202708	

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.