



P502476

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	102 mm (4.02 inch)
Thread Size	1-12 UN
Length	150 mm (5.91 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	88 mm (3.46 inch)
Efficiency 50%	17 micron
Efficiency 95%	27 micron
Efficiency 99%	39 micron
Efficiency Test Std	ISO 4548-12

Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	0.8 bar (12 psi)
Bypass Valve Setting HR	1 bar (15 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	MITSUBISHI 32B4020100

Other Information

UPC Code	742330202715
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.