



## P502596

### LUBE FILTER, SPIN-ON FULL FLOW

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

#### Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	M30 x 2
Length	237 mm (9.33 inch)
Gasket OD	103 mm (4.06 inch)
Gasket ID	92.6 mm (3.65 inch)
Efficiency 50%	9 micron
Efficiency 99%	21 micron
Efficiency Test Std	ISO 4548-12
Anti-Drainback Valve	Yes

Bypass Valve	Yes
Bypass Valve Setting LR	2.4 bar (35 psi)
Bypass Valve Setting HR	2.6 bar (38 psi)
Media Type	Cellulose
Collapse Burst	6.86 bar (99 psi)
Primary Application	LIEBHERR 10297295

---

#### Other Information

UPC Code	742330989401
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.