



Product Specifications



P550086

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1 1/8-16 UN
Length	167 mm (6.57 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	90 mm (3.54 inch)
Efficiency 50%	20 micron
Efficiency Test Std	ISO 4572
Bypass Valve	Yes
Bypass Valve Setting LR	1.8 bar (26 psi)

Bypass Valve Setting HR	2.1 bar (30 psi)
Media Type	Cellulose
Collapse Burst	10 bar (145 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	KOMATSU 6136515120

Other Information

UPC Code	742330040768
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.