

## P550222

### HYDRAULIC FILTER, SPIN-ON

#### Why Choose Donaldson Spin-On Filters

- High-performance Hydraulic Spin-On filters utilize Donaldson media technology which undergoes stringent design and testing which sets the standard in filtration performance.
- Donaldson Media Formulations provide superior hydraulic system protection.
- Donaldson offers the largest selection of replacement hydraulic Spin-On filters for greater contamination control
- A variety of filters which meet and/or exceed OEM specifications



#### Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	3/4-16 UN
Length	136.2 mm (5.36 inch)
Gasket OD	72 mm (2.83 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency Beta 2	17 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes

Bypass Valve	Yes
Bypass Valve Setting LR	0.5 bar (7 psi)
Bypass Valve Setting HR	0.7 bar (10 psi)
Style	Spin-On
Media Type	Cellulose
Primary Application	ALLISON 25010543

---

#### Other Information

UPC Code	742330041604
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.