



P550341

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	141 mm (5.55 inch)
Thread Size	1 1/2-16 UN
Length	310 mm (12.20 inch)
Gasket OD	111 mm (4.37 inch)
Gasket ID	100 mm (3.94 inch)
Efficiency 50%	25 micron
Efficiency Test Std	SAE J1858
Bypass Valve	Yes
Bypass Valve Setting LR	2.2 bar (32 psi)

Bypass Valve Setting HR	2.8 bar (41 psi)
-------------------------	------------------

Media Type	Cellulose
------------	-----------

Collapse Burst	4.1 bar (59 psi)
----------------	------------------

Type	Full-Flow
------	-----------

Style	Spin-On
-------	---------

Primary Application	DAF 267714
---------------------	------------

Other Information

UPC Code	742330042243
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.