



P550367

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	136 mm (5.35 inch)
Thread Size	M36 x 1.5
Length	308 mm (12.13 inch)
Gasket OD	110 mm (4.33 inch)
Gasket ID	100 mm (3.94 inch)
Efficiency 99%	21 micron
Efficiency Test Std	SAE J1858
Bypass Valve	Yes
Bypass Valve Setting LR	1.8 bar (26 psi)

Bypass Valve Setting HR	2.1 bar (30 psi)
Media Type	Cellulose
Collapse Burst	10.3 bar (149 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	NAVISTAR 1819452C1

Other Information

UPC Code	742330042342
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.