



P551402

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	135 mm (5.31 inch)
Thread Size	1 1/2-16 UN
Length	308 mm (12.13 inch)
Gasket OD	109 mm (4.29 inch)
Gasket ID	100 mm (3.94 inch)
Efficiency 99%	21 micron
Efficiency Test Std	ISO 16889
Bypass Valve	Yes
Bypass Valve Setting LR	2.2 bar (32 psi)

Bypass Valve Setting HR	2.7 bar (39 psi)
Media Type	Cellulose
Type	Full-Flow
Style	Spin-On
Primary Application	Vertical installation only – Threads at the top

Other Information

UPC Code	742330111642
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.