

Product Specifications



P552100

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	118 mm (4.65 inch)
Thread Size	1 5/8-12 UN
Length	260 mm (10.24 inch)
Gasket OD	110 mm (4.33 inch)
Gasket ID	98 mm (3.86 inch)
Efficiency 99%	21 micron
Efficiency Test Std	SAE J1858
Media Type	Cellulose
Collapse Burst	10.3 bar (149 psi)
Gasket ID Efficiency 99% Efficiency Test Std Media Type	98 mm (3.86 inch) 21 micron SAE J1858 Cellulose

Туре	Full-Flow
Style	Spin-On
Primary Application	DETROIT DIESEL 23518480

Other Information

UPC Code	742330044094	

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.