



Product Specifications



P554770

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	76 mm (2.99 inch)
Thread Size	3/4-16
Length	120 mm (4.72 inch)
Gasket OD	70 mm (2.76 inch)
Gasket ID	60 mm (2.36 inch)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	1.8 bar (26 psi)
Bypass Valve Setting HR	2.1 bar (30 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	JOHN DEERE AM34770

Other Information

UPC Code	742330044759
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.