

Product Specifications

P566660

HYDRAULIC FILTER, CARTRIDGE DT



Why Choose Donaldson DT Filters

High-performance DT Hydraulic Cartridges utilize Donaldson Synteq™ media technology which extends filter life, allows a higher initial cleanliness, and provides superior hydraulic system protection.

- ullet DT hydraulic filters help protect equipment, reduce maintenance cost and increase equipment uptime \Box which has a direct impact on your bottom line.
- DT filters offer the best available chemical resistance for hydraulic applications.
- A high dirt holding capacity provides longer filter life \square for extended filter change intervals, reducing time and expense for servicing equipment
- Fluorocarbon seals are standard on all Donaldson DT filters.

Attributes

| Seal Material | Viton |
|----------------------|----------------------|
| Outer Diameter | 47.75 mm (1.88 inch) |
| Inner Diameter | 22.2 mm (0.87 inch) |
| Overall Length | 152.7 mm (6.01 inch) |
| Efficiency Beta 1000 | 12 micron |
| Collapse Burst | 31 bar (450 psi) |

| Style | Cartridge |
|---------------------|---------------------|
| Brand | DT High-Performance |
| Media Type | Synthetic |
| | |
| Packaged Dimensions | |
| Packaged Length | 2.3 IN |
| Packaged Width | 2.3 IN |
| Packaged Height | 10.4IN |
| Packaged Weight | 0.42 LB |
| Packaged Volume | 0.0318 FT3 |

Other Information

| NMFC Code | 069100-06 |
|-----------|--------------|
| UPC Code | 742330179222 |

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.