



P577086

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	M27 x 2
Length	102 mm (4.02 inch)
Gasket OD	71.5 mm (2.81 inch)
Gasket ID	61.5 mm (2.42 inch)
Efficiency 90%	35 micron
Efficiency Test Std	ISO4548/12
Stand Pipe	Yes Y/N
Bypass Valve	Yes

Bypass Valve Setting LR	2.07 bar (30 psi)
Bypass Valve Setting HR	2.55 bar (37 psi)
Media Type	Cellulose
Style	Spin-On
Primary Application	CNH 87679598

Other Information

UPC Code	742330994351
----------	--------------

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.